

Approved for Zone 0. The redesigned Survivor features a low-profile bezel that doesn't interfere with gear and equipment. Its spring-loaded clip securely grabs onto gear, and the reinforced D-ring allows your light to hang forward.



Low-profile design doesn't interfere with gear and equipment



Interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation

Rubber dome push-button switch easy to use with gloves

Specialized optic combines low profile with strong performance and a wide beam

Rugged nylon polymer body is virtually indestructible

DUAL POWER SOURCE:
Rechargeable lithium ion battery; also accepts 4 "AA" alkaline or lithium batteries



<p>High, low, emergency flash and moonlight modes:</p> <ul style="list-style-type: none"> – High for a super-bright beam that pierces through smoke: 41,000 candela; 175 lumens; 405m beam distance; runs 3.5 hours (lithium rech); runs 8 hours (AA alkaline or AA lithium) – Low for bright light and longer run time: 14,000 candela; 60 lumens; 237m beam distance; runs 10 hours (lithium rech); runs 20 hours (AA alkaline or AA lithium) – Flash for signaling: runs 5 hours – Moonlight mode provides low-level lighting for battery conservation: runs 15 days <p>Optimized electronics provide regulated intensity</p>
<p>Unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy-duty bezel</p>

<p>FTZU 15 ATEX 0046X; IEC Ex FTZU 15.0029X II 1G Ex ia op is IIB T3/T4 Ga; II 2G Ex ia op is IIC T3/T4 Gb INMETRO: DNV 16.0014X; Ex ia op is IIB T3/T4 Ga; Ex ia op is T3/T4 Gb</p>
<p>IP66 rated design; dust tight and water resistant; 2 meter impact resistance tested</p>
<p>17.92 cm; 388g (with lithium rechargeable or AA alkaline); 354g (with AA lithium)</p>
<p>Limited Lifetime Warranty Visit streamlight.com for full warranty information</p>
<p>See reverse for item numbers</p>

90562	Survivor - 230V AC/12V DC cords (ATEX/IECEX) - Orange
90580	Survivor - 230V AC/12V DC cords (INMETRO) - Orange
90563	Survivor - 240V AC/12V DC cords (ATEX/IECEX) - Orange
90564	Survivor - 100V AC/12V DC cords (ATEX/IECEX) - Orange
90565	Survivor - 12V DC Fast Charge (ATEX/IECEX) - Orange
90566	Survivor - (WITHOUT CHARGER) (ATEX/IECEX) - Orange
90581	Survivor - (WITHOUT CHARGER) (INMETRO) - Orange
90567	Survivor - Alkaline Model (ATEX/IECEX) - Orange
90582	Survivor - Alkaline Model (INMETRO) - Orange
90316	Lithium Ion Battery Pack

