

SPECIFICATIONS

Product Description: AMBIENT AIR PUMP A-3000ATE

Part Number: 9846

Style: ROTARY VANE

GENERAL DESCRIPTION:

Portable air source for up to six full or half face respirator users or four hood users. Solid performance in multi-worker applications, cleaning, sanding or chemical handling operations.

CONSTRUCTION:

Rigid metal base & housing with locking 4" (10.1cm) caster wheels

Brass & galvanized steel plumbing

 Quick-connect Rectus (OBAC) air fittings (other fittings available upon request)

Adjustable pressure relief valve

Pressure gauge

Steel belt guard & handle

Powder coated gray



PUMP:

Type: Oil-less, rotary vane, belt driven

Vanes: Carbon construction (4 ea/ replaceable) (4.5" (11.43cm) X 1.8" (4.76cm)

X 0.25" (.63cm)

Inlet Filter: 50 Micron felt material Exhaust Filter: 0.3 Micron HEPA

Working Pressure: 2-12 psi (.14-.83 bar) (15 psi (1.03 bar) max)

Performance: 0-32 CFM (0-54.36 m³/hr) (adjusted via pressure relief valve)

Airline length: 100 feet (30.4m) maximum from pump to respirator (sold separately)

Noise level: At Pump: 105 dB At 6 feet (1.82m): 90 dB

At 10 feet (3.04m): 85 dB

MOTOR:

Type: 3 HP UL Listed, CSA Certified, TEFC continuous duty

Volts: 1 15V/230V AC Single Ø, 60 Hz Current Draw: 33.6A @ 115V (16.8A @ 230V)

NEMA Nom Eff: 77

Cord: 10' (3.04m) 10/3 AWG S00W-A 600V Neoprene heavy duty

Switch: External ON/OFF

Plug: NEMA L5-30P (L6-30P in 230V configuration)

DIMENSIONS:

Length	Width	Height	Weight
In (cm)	In (cm)	In (cm)	In (cm)
30" (76.2)	17" (43.1)	24" (60.9)	217 lbs (98.42)