Product Data Sheet

BUTYL DRYBOX

B1532 and B1532A

artnr. NxB1532





| Description: | Laminate Butyl Drybox gauntlet. The gauntlet is 0.38 mm thick and 815 mm long with an handed or ambidextrous shape, providing two working surfaces. They are designed for use in wet environment drybox conditions and are available with a rolled cuff for a 5" 7" or 8" port on the drybox. Superior chemical resistance provided by the Butyl rubber. | | | |
|---|--|---|----------------------------------|---|
| Dimensions: | Length: Sizes Available: | B1532/B1532A = 815 mm 8.5 = (8.5), 9.75 = (9.5), 10.5 = (9.5-10) (EN420) | | |
| Materials: | Butyl rubber laminate gauntlet. | | | |
| Standards: | 0120 CE. EN420, EN388, EN374. | | | |
| *Mechanical Performance to EN388: | Abrasion Blade Cut Tear Puncture | Level 0 Level 0 Level 1 Level 1 | SGS, YAR Camberley | g performed by: SLEY I.C.S., y, Surrey GU15 3EY ody No: 0120 |
| *Penetration to | EN374: | Level 3 | | |
| *Chemical Performance to EN374: | <u>Reagent</u> Chloroform Acetone 98% Sulphuric A Hexane | cid | <u>Level</u> 1 6 6 1 | <u>Time</u> 15 min > 8 hrs > 8 hrs 15 min |
| Packaging: | 1 glove Ambidex 1 pair handed | trous | | |
| | | | PDS 24-1 | 11-2000 |

North Safety Products Europe by postbus 5016, 4330KA, Middelburg - Holland