

# X500

**bolle**  
TACTICAL

Available with interchangeable lenses, the X500 goggle is the ideal model for extreme situations. It can be worn over prescription spectacles and the X500 goggle provides optimal comfort thanks to its anti-fog treatment and maximum protection against stones and splinters.

réf. X500I

Double lens

Coatings anti-scratch,  
anti-fog, anti-static

141 g

10 mm comfort foam and ventilators

Adjustable large strap



X500I (Complete product)



FAX5I (Spare lens only)



FAX5J (Spare lens only)



FAX5F (Spare lens only)

Europe Bollé Safety  
95 Rue Louis Guérin  
69100 Villeurbanne - France  
tel: 00 33 (0) 4 78 85 23 64  
fax: 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park  
Leatherhead Road - Chessington  
Surrey - KT9 2NY  
tel. 00 44 (0)208 391 4700  
fax 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**TACTICAL**

**Ballistic Resistance  
STANAG 2920**

**V50 : 670 km/h (186 m/s)**

www.bolle-safety.com

STANDARD MARKINGS :

| Products Ref. | LENSES                       |                             |                       |                 |                   |              |                         |                              |                            |                            |                               |   |              | FRAMES  |                       |           |                |              |                                  |   |                               |                          |                              |                            |         |
|---------------|------------------------------|-----------------------------|-----------------------|-----------------|-------------------|--------------|-------------------------|------------------------------|----------------------------|----------------------------|-------------------------------|---|--------------|---------|-----------------------|-----------|----------------|--------------|----------------------------------|---|-------------------------------|--------------------------|------------------------------|----------------------------|---------|
|               | Risks relating to radiations |                             | Bollé Protection Logo | Optical Quality |                   |              | Mechanical Risks        |                              |                            | Electrical Risks           | Thermal Risks                 | Coatings (Optional marking K: anti-scratch N: anti-fog) |              | CE logo | Bollé Protection logo | Standards | Chemical Risks |              |                                  | Electrical Risks                        | Mechanical Risks              |                          |                              | Thermal Risks              | CE logo |
|               | EN 170 - UV                  | EN 172 - Solaires (100% UV) |                       | Permanent Wear  | Intermittent Wear | Short Period | Low energy Impact 5 m/s | Medium energy Impact 120 m/s | High energy Impact 190 m/s | Extreme temperature impact | Electric arc short circuiting | Molten metals and hot solids                            | anti-scratch |         |                       |           | anti-fog       | Liquid drops | Large dust particles > 5 microns | Gas and fine dust particles < 5 microns | Electric arc short circuiting | Low energy impact 45 m/s | Medium energy impact 120 m/s | High energy impact 190 m/s |         |
| X500I         |                              |                             | ☞                     | 1               |                   |              | B                       | N/A                          | T                          | N/A                        | N/A                           | ☞   | ☒            | ☞       | EN 166                |           |                |              | N/A                              |   | B                             | N/A                      | T                            | N/A                        | ☞       |
| FAX5I         |                              |                             | ☞                     | 1               |                   |              | B                       | N/A                          | T                          | N/A                        | N/A                           | ☞   | ☒            | N/A     | N/A                   | N/A       | N/A            | N/A          | N/A                              | N/A                                     | N/A                           | N/A                      | N/A                          | N/A                        | N/A     |
| FAX5J         |                              | 5-1.4                       | ☞                     | 1               |                   |              | B                       | N/A                          | T                          | N/A                        | N/A                           | ☞   | ☒            | N/A     | N/A                   | N/A       | N/A            | N/A          | N/A                              | N/A                                     | N/A                           | N/A                      | N/A                          | N/A                        | N/A     |
| FAX5F         |                              | 5-2.5                       | ☞                     | 1               |                   |              | B                       | N/A                          | T                          | N/A                        | N/A                           | ☞   | ☒            | N/A     | N/A                   | N/A       | N/A            | N/A          | N/A                              | N/A                                     | N/A                           | N/A                      | N/A                          | N/A                        | N/A     |

N/A: Non applicable



V50 : 670 km/h (186 m/s)



V50 : 637 km/h (177 m/s)



V50 : 644 km/h (179 m/s)

CHARACTERISTICS :

|              |   |
|--------------|---|
| Double-Lens  | Outer: PC anti-scratch- 2.0 mm<br>Inner: Acetate anti-fog - 0.5mm |
| Frame        | TPU   |
| Spare Lenses | Available in clear, smoke and yellow                              |
| Strap        | Adjustable, 45 mm wide with a double insert                       |
| Foam         | 10 mm and ventilators   |

PACKAGING AND EAN 13 CODE :

|                                  |               |
|----------------------------------|---------------|
|                                  | X500I         |
| individual carton box            | 3660740002725 |
| N/A                              | N/A           |
| 60 safety goggles per outer pack | 3660740202729 |

PACKAGING AND EAN 13 CODE :

|                                   |               |               |               |
|-----------------------------------|---------------|---------------|---------------|
|                                   | FAX5I         | FAX5J         | FAX5F         |
| individual carton box             | 3660740001544 | 3660740001551 | 3660740001537 |
| 15 spare lenses per box           | 3660740101541 | 3660740101558 | 3660740105034 |
| 150 safety goggles per outer pack | 3660740201548 | 3660740201555 | 3660740201531 |

Notified laboratories for certification :



Banc Officiel d'Epreuve Saint-Etienne

