

# X800

**bolle**  
TACTICAL

Compatible with all types of helmets, the X800 goggle is perfectly advisable for extreme situations. Lightweight, low profile and fitted with a panoramic lens, the X800 offers increased protection. Ventilated, the X800 goggle offers the best level of fog resistance.

réf. X800I

Panoramic visual field

Coatings anti-scratch,  
anti-fog, anti-static

Bi-material frame

106 g



X800I (Complete product)



FAX8I (Spare lens only)



FAX8J (Spare lens only)



FAX8F (Spare lens only)

Optical Insert available  
Ref: SOSX800

Adjustable large strap

Europe Bollé Safety  
95 Rue Louis Guérin  
69100 Villeurbanne - France  
tel: 00 33 (0) 4 78 85 23 64  
fax: 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park  
Leatherhead Road - Chessington  
Surrey - KT9 2NY  
tel. 00 44 (0)208 391 4700  
fax 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**TACTICAL**

**Ballistic Resistance  
STANAG 2920**

**V50 : 652 km/h (181 m/s)**

[www.bolle-safety.com](http://www.bolle-safety.com)

STANDARD MARKINGS :

Products Ref.	LENSES												FRAMES										
	Risks relating to radiations		Optical Quality	Mechanical Risks				Electrical Risks	Thermal Risks	Coatings (Optional marking K: anti-scratch N: anti-fog)		CE logo	Bollé Protection Logo	Standards	Chemical Risks			Electrical Risks	Mechanical Risks			Thermal Risks	CE logo
	EN 170 - UV	EN 172 - Solaires (100% UV)		Permanent Wear	Intermittent Wear	Short Period	Low energy impact 5 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extreme temperature impact	Electric arc short circuiting				Molten metals and hot solids	anti-scratch	anti-fog	Liquid drops	Large dust particles > 5 microns	Gas and fine dust particles < 5 microns	Electric arc short circuiting	Low energy impact 45 m/s	
X800I			1			B	N/A	T	N/A	N/A			EN 166				N/A	B	N/A	T	N/A	CE	
FAX8I			1			B	N/A	T	N/A	N/A			N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
FAX8J	5-1.1		1			B	N/A	T	N/A	N/A			N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
FAX8F	5-2.5		1			B	N/A	T	N/A	N/A			N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	

N/A: Non applicable



V50 : 637 km/h (177 m/s)



FAX8J



V50 : 652 km/h (181 m/s)

CHARACTERISTICS :

Lens	Clear PC - 2.33 mm - Curve 5
Frame	Bi-material (Nylon + TPE)
Spare Lenses	Available in clear, smoke and yellow
Strap	Adjustable, 35 mm wide in nylon
Foam	No
Case	Black

PACKAGING AND EAN 13 CODE :

	X800I
individual carry case	3660740002749
N/A	N/A
60 safety goggles per outer pack	3660740202743

PACKAGING AND EAN 13 CODE :

	FAX8I	FAX8J	FAX8F
individual carry case	3660740001575	3660740001582	3660740001568
30 spare lenses per inner box	3660740101572	3660740101589	3660740101565
300 spare lenses per outer pack	3660740201579	3660740201586	3660740201562

Notified laboratories for certification :

