## **HIGH PRESSURE LIFTING BAGS 8.0 bar**

Sava high-pressure lifting bags are Kevlar cord reinforced. The patented construction utilizes a state-of-the-art design and guarantees an excellent operation and high lifetime. Metal parts are solid brass.

The bags are thin, light and simple for use. A special dimpled surface assures a good gripping even when two bags are stacked on top of each other. There are

fifteen sizes of lifting bags available both square and rectangular shape with a lifting capacity between one and 64 tons.

The application range of Sava standard lifting bags is further expanded by the industrial lifting bags and custom-made bags for special applications, respectively.














Code	Description	Quantity	Weight (kg)	
77973	Lifting bag, Type SLK 1/7	1 x	0.6	
77974	Lifting bag, Type SLK 3/13	1 x	1.3	
77975	Lifting bag, Type SLK 6/15	1 x	2.4	
517967	Inflation hose, 5m, yellow	1 x	0.8	
523002	Air compressed cylinder 200bar, 1I	1 x	3.0	
523000	Inflation and safety device with fingertight connection, pressure reducer, pressure gauge, safety valve and inlet	1 x	1.1	
522999	Inflation distributor with two 1m inflation hoses, yellow	1 x	0.6	
528871	Portable case 600x400x135	1 x	3.4	


High Pressure lifting Bags 8.0 bar												
Model	EU	SLK 1/7	SLK 3/13	SLK 6/15	SLK 8/18	SLK 12/22	SLK 19/27	SKL 24/30	SLK 31/36	SLK 40/42	SLK 54/65	SLK 64/51
Art. Number		77973	77974	77975	76734	76735	76736	76737	76738	76739	76794	76740
Size	cm x cm	15 x 15	22.5 x 22.5	30 x 30	38 x 38	45 x 45	55 x 55	61 x 61	69 x 69	78 x 78	87 x 87	91 x 91
Thickness	mm	28	28	28	28	28	28	30	30	30	30	30
Weight	kg	0.6	1.3	2.4	4.0	5.3	8.1	11.2	13.3	18.2	22.5	25.3
Insertion height	mm	29	29	29	29	29	29	31	31	31	31	31
Max. lifting height	cm	7	13	15	18	22	27	30	36	42	45	51
Max. lifting capacity	kg	1000	2820	5750	9620	12650	20250	24690	31410	41285	52345	65900
Nominal content	1	0.6	1.7	4.7	9.6	16.9	32.9	46.2	69.0	102.3	145.0	167.2
Max. air requirement	1	5	15	42	86	152	296	416	621	921	1305	1505
Max. inflation pressure	bar	8	8	8	8	8	8	8	8	8	8	8
Test pressure	bar	12	12	12	12	12	12	12	12	12	12	12
Bursting pressure	bar	>32	>32	>32	>32	>32	>32	>32	>32	>32	>32	>32
Inflation time	sec	0.6	1.2	2.0	5.0	7.0	15.0	20.0	28.0	50.0	65.0	80.0

Model	EU	SLK-L 24/20	SLK-L 9/18	SLK-L 13/23	SLK-L 20/23
Art. Number		77983	519833	519834	519837
Size	cm x cm	32 x 102	30 x 45	37.5 x 50	37.5 x 75
Thickness	mm	28	28	28	28
Weight	kg	8.5	3.5	4.9	7.4
Insertion height	mm	29	29	29	29
Max. lifting height	cm	20	18	23	23
Max. lifting capacity	kg	24000	9600	13600	20700
Nominal content	I	24.0	10.6	20.0	29.8
Max. air requirement	I	220	95	170	270
Max. inflation pressure	bar	8	8	8	8
Test pressure	bar	12	12	12	12
Bursting pressure	bar	>32	>32	>32	>32
Inflation time	sec	12.0	6.0	8.0	14.0






max. lifting capacity 10kN =1t



max. lifting capacity



## **HIGH PRESSURE LIFTING BAGS 8.0 bar**

