



## Cap Mount Ear Muffs

QuickSnap™ Ear Muffs for Attachment to Safety Helmets

Hearing Protection and other Safety Equipment are many times incompatible. Product designers simply did not plan for the real world. Head, Face and Hearing protection products can in fact be worn simultaneously with Elvex Quick Snap System! Cap Mount Ear Muffs and Face Shields are functionally integrated.



## Ear Muffs for Safety Helmets

- Highest NRR cap mount ear muff available, up to 28 NRR
- Choice of NRR levels: 24, 25, 27 and 28 dB
- Universal blade fits most slotted safety caps
- Dielectric construction
- Integrates with a variety of face shields
- Can be attached to non slotted safety caps
- Most functional system on the market



Elvex ear muffs for mounting on safety helmets and safety caps are available in a wider selection of models and higher performance ratings than any other ear muffs from any manufacturer on the US market. Cap mount muffs are available with Noise Reduction Ratings (NRR) from 24 to 28 dB.





ANSI S3-19-1974, Dr. Michael & Associates, Certified and independent laboratory,  
State College, Pennsylvania, USA

**HM-2593**

Frequency, Hz	125	250	500	1000	2000	3150	4000	6000	8000	H	M	L	NRR
Mean Attenuation, dB	15.2	19.0	30.7	35.0	35.1	35.2	32.6	35.8	36.2	32	27	19	24
Std. Deviation	2.0	2.4	2.5	2.7	2.8	1.6	2.2	2.7	3.5				

**HM-2093**

Frequency, Hz	125	250	500	1000	2000	3150	4000	6000	8000	H	M	L	NRR
Mean Attenuation, dB	18.5	21.2	32.1	35.3	36.6	38.1	37.9	39.1	37.8	35	29	22	25
Std. Deviation	3.3	2.7	3.0	2.7	3.3	2.7	2.9	4.0	2.9				

**HM-6093**

Frequency, Hz	125	250	500	1000	2000	3150	4000	6000	8000	H	M	L	NRR
Mean Attenuation, dB	19.4	24.5	33.7	35.7	34.5	36.0	40.9	39.3	37.9	35	31	24	27
Std. Deviation	3.2	2.3	2.8	3.0	2.3	1.7	2.8	2.5	3.4				

**HM-8093**

Frequency, Hz	125	250	500	1000	2000	3150	4000	6000	8000	H	M	L	NRR
Mean Attenuation, dB	20.5	24.8	32.8	36.2	35.4	37.9	41.3	36.6	37.5	35	32	25	28
Std. Deviation	2.6	1.6	2.2	2.9	2.2	2.9	3.0	2.4	2.8				