## **Product Data Sheet**

## NEO TASK NEOPRENE GLOVE SERIES





Safety Products

Description: Heavy duty Neoprene gloves, liquid proof, with smooth and rough

finish in lengths from 300 - 450 mm depending on the degree of

protection required.

Materials: 100% Neoprene coating with cotton interlock liner

Articles: T1241 smooth, length 30 cm, (12") T1241WG, same but rough

T1441 smooth, length 35 cm (14") T1441WG,same but rough

T1841 smooth, length 45 cm (18") T1841WG, same but rough

Size: 11XXL

Standards: EN420.2003, EN388.2003, EN374.2003

**CE Category : Complex Design** 



MECHANICAL DATA CHEMICAL DATA

Abrasion resistance level 3 Test EN-374-3 measures the BREAK

Blade cut resistance level 1 THROUGH TIME (B.T.T) for a

Tear resistance level 2 chemical to permeate through a glove

Puncture test level 1 material.

Chemicals	B.T.T (Min)	Class
Methanol	> 60	3
40% Sodium hydroxide	>480	6
96% Sulphuric Acid	> 60	3

B.T.T. is defined as the time at which one micro-gram of a chemical permeate per square centimetre per minute through the glove palm sample (1µgm/cm²/min.).

Packaging: T1241-WG and T1441-WG 12 pairs per bag, 72 pairs per case

T 1841-WG 6 pairs per bag, 36 pairs per case