

Bright Star Lighting Products

www.flashlight.com

Engineering Data Sheet: 19111, 19112, 19114

Unit Information

Model #: 19111/19112/19114
UPC-IC: 1673119111/12/14

Unit Dimensions

Length: 11 in.
Width: 5 in.
Height: 4 in.

Master Pack Dimensions

Weight: 11 lbs.
Cube Dimensions: 14.5 in x 11.5 in x 13 in
Quantity: 3

Specifications

Ni-Cad Battery: 3.6 V, 1.6 Ah
Power Source: 120V AC
12-24V DC
Weight: (w/ Ni-Cad Battery Pack): 12oz
Weight: (w/ Alkaline Batteries): 14oz
Approximate Burn Time w/ Ni-Cad battery pack: 1-1/2
- 2 hours

Safety Approvals

UL: Class I, Division 1, Group D
Class I, Division 2 Group A,B,C,D
Class II, Division 2 Group G
Operating Temp Code: T3A

CSA: Class I, Division 2, Group A,B,C,D
Class II, Division 2, Group G
Operating Temp Code: T3

MSHA Approved

Components

- Super Tough Nylon Housing
- Microprocessor Controlled Circuit Board w/ LED Status Indication
- Co-Axial AC Power Pack
- Automotive DC Power Cord

Product Features

- DC Input: 12/24V DC Vehicular Adapter (Fire Trucks)
- AC Input: 120V AC Adapter (US/North America)
240V AC Adapter (Euro or UK)
- Flashlight Receives Priority Charge
- Wall & Vehicle Mountable
- Microprocessor Controlled
- Super Tough Nylon
- LED Status Indication
 - RED: Charging
 - GREEN: Fully Charged
 - AMBER: Standby
 - FLASHING RED: Fault
- 2-Hour Charging Time
- Safe to Touch Charging Contact
- Dual Power Supply



Accessories

<u>Accessories</u>	<u>Description</u>
500299	Charger Base
500202-N	Ni-Cad Battery Pack
20641	120V AC Adapter
500180	12-24V DC Adapter
23853	6 1/2" Red Snap In Wand
23860	6 1/2" Yellow Snap In Wand