



www.flashlight.com

Engineering Data Sheet: 500221

Unit Information

Model #: 500221 6 Div I (Orange)

Master Pack Dimensions

Weight: 12 lbs.
 Cube Dimensions: 14.5 in x 11.5 in x 13 in
 Quantity: 3

Specifications

Ni-Cad Battery: 4.8 V, 1.6 Ah
 Power Sources options: 120V or 220V AC
 12-24V DC
 Weight: (w/ Alkaline Batteries): 1 lb.
 Weight: (w/ Ni-Cad Battery Pack): 1lb
 Bulb/Lamp Life: 50 hours
 Light Output: 45,000 beam candlepower

Components

- Super Tough Nylon Housing
- Microprocessor Controlled Circuit Board w/ LED Status Indication
- Co-Axial AC Power Pack
- Automotive DC Power Cord

Product Features

- DC Input: 12/24V DC Vehicular Adapter (Fire Trucks)
- AC Input: 120V AC Adapter (US/North America)
 220-240V AC Adapter (Euro or UK)
- Flashlight Receives Priority Charge
- Wall & Vehicle Mountable
- Microprocessor Controlled
- Super Tough Nylon
- LED Status Indication
 - RED: Charging
 - GREEN: Fully Charged
 - AMBER: Standby
 - FLASHING RED: Fault
- 2-Hour Charging Time
- Safe to Touch Charging Contacts

Unit Dimensions

Length: 11 in.
 Width: 4 in.
 Height: 12 in.

Safety Certifications:

UL: Class I, Div 1, Group D
 Operating Temp T3
 ATEX II 2 G EEX ib e IIB T3



**Item # 500221
 Div I (Orange)**

