

# COMFORT

900111, 900112, 900113

A single-piece lens offering excellent coverage with a stylish design.

Ultra-lightweight and attractive shape, offering protection without compromise.

CE EN 166 : 2001 EN 170



900  
111



900  
112



900  
113

## Main Applications

- General industry – Maintenance
- Building construction
- Regular or intensive use

## Main Features

- Perfect fit for optimal protection
- Ultra lightweight
- Suspended nose-bridge
- Extra flat temples – easy to put on

## Engraved Markings

- Clear: 2C-1.2 RSG 1FT
- Indoor /Outdoor: 2-1.2 RSG 1FT
- Smoke: 5-2 RSG 1FT
- Temples: RSG CE EN 166FT

Reference	900 111	900 112	900 113
Frame Material	PC polycarbonate	PC polycarbonate	PC polycarbonate
Lens Material	PC polycarbonate	PC polycarbonate	PC polycarbonate
Lens Base Curve (mm)	9.5	9.5	9.5
Lens Thickness (mm)	2.2	2.2	2.2
Anti-Scratch	 anti scratch	 anti scratch	 anti scratch
Anti-Fog	 anti fog	 anti fog	 anti fog
Weight (g)	24	24	24
Soft Nose Pad	 soft nose pad	 soft nose pad	 soft nose pad
Vented	-	-	-
Suitable for use with prescription glasses	-	-	-
Air/watertight	-	-	-
Lens Markings	2C-1.2 1FT	5-2 1FT	2-1.2 1FT
Frame Markings	CE EN 166 FT	CE EN 166 FT	CE EN 166 FT
Quantity per box	10	10	10
Quantity per full carton	300	300	300