

Technical Data Sheet

MicroMAX NS Non-Slip Overshoe


Product Description	Non-slip overshoe in MicroMAX NS fabric. Elasticated ankles. EMN022 - 31cm. EMN22NSLarge - 31cm. EMN22NSXL - 31.50cm. EMN22NSXXXL - 41cm all measurements refer to the length of sole.
Material	62gsm microporous polyethylene film / spunbond PP laminate with textured PVC sole
Seam Type	Three thread overlock
Colour	White (cream sole)

<u>CE Standards</u>	Description	Approved
EN 340: 2002	Overshoes and overboots are designed primarily to protect the environment from the user rather than to provide the user with protection.	
EN 13034 Type 6		

Physical Properties (Upper fabric only - not sole)					Particle Barrier - Aloxite Method *	
Test No	Description	Units	Result	EN Class	Particle Size	Flux
EN 530	Abrasion Resistance	cycles	>10<100	1	1.0 - 1.5 mu	0
EN 863	Puncture Resistance	N	6.2	1	1.5 - 2.0 mu	2
ISO 2960	Bursting Strength	KN/M ²	50.9	1	2.0 - 2.5 mu	1
ISO 7854	Flex Cracking Resistance	cycles	>15<40k	4	2.5 - 3.0 mu	0
ISO 9073	Trapezoidal Tear Strength md/cd	N	40.6/16.7	3/1	3.0 - 3.5 mu	0
EN 5082	Seam Strength	N	88.8	3	> 3.5 mu	0
EN 1149-1	Surface Resistivity	ohms	1.3x10 ⁹ (inside)		<i>* Applies to fabric only</i> <i>* Anomalies can occur if particles coagulate downstream of the fabric and are counted as larger particles</i>	

Liquid Chemical Repellency and Permeation (Upper fabric only)

Test No	Description	Chemical	Repellency %	Penetration %
EN863	Chemical Repellency	Sulphuric Acid 30%	0	97.7
	(For Type 6 garments)	Sodium Hydroxide 10%	0	99.1



Textured PVC sole

For Further information please contact
lakeland Europe on +44 1430 478140 or
sales-europe@lakeland.com

Lakeland Industries Europe Ltd
 Jet Park 2, 244 Main Road, Newport, East Yorkshire
 United Kingdom
 Tel: +44 1430 478140 / Fax: +44 1430 478144
 sales-europe@lakeland.com