

# SOLIS

## SIMPLICITY AND PROTECTION

Meeting all protective requirements, SOLIS features a non-slip bridge and temples for permanent wear.



SOLIPSF



SOLIFLASH



SOLIPOL



25 g

**SUPPLIED WITH**

Microfibre pouch  
ETUIFS



- + NON-SLIP BRIDGE**
- + NON-SLIP TIPGRIP TEMPLES**
- + ANTI-STATIC (ACCORDING TO VERSION)**

**bollé**  
SAFETY

# SOLIS

## SIMPLICITY AND PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SOLIS	 Clear	SOLIPSF	5-3,1  1 F €€	 EN166 F €€	Anti-scratch/anti-fog
	 Blue flash	SOLIFLASH	5-3,1  1 F €€	 EN166 F €€	Anti-scratch
	 Polarized	SOLIPOL	5-3,1  1 F €€	 EN166 F €€	Anti-scratch

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

#### Others symbols:

€€ European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

€€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### TECHNOLOGY

#### B-ESP

ESP, Extra Sensory Perception.  
An innovative coating to reduce dazzle and the harmful affects of blue light.  
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

#### B-POLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

### PACKAGING AND EAN13 CODE

	SOLIPSF	SOLIFLASH	SOLIPOL
Individual plastic bag	3660740003586	3660740003593	3660740003722
10 safety spectacles per inner box	3660740103583	3660740103590	3660740103729
300 safety spectacles per outer pack	3660740203580	3660740203597	3660740203726

### CHARACTERISTICS

LENSES	PC - 2,0 mm - Curve 8
FRAME	Nylon
TEMPLES	PA + TPR
STRAP	No
FOAM	No
SPARE LENSES	No



01/10/2013

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY