

UNIVERSAL

PROTECTION FOR ALL

The wrap-around UNIVERSAL model adapts to all face shapes thanks to its B-Flex bridge and pivoting temples.



UNIPSI



UNIPSF



26 g

SUPPLIED WITH

Adjustable cord
CORDC










- + **b FLEX BRIDGE**
- + **UPPER PROTECTION**
- + **PIVOTING TEMPLES**
- + **COINJECTED STRAIGHT TEMPLES**

bollé
SAFETY

UNIVERSAL

PROTECTION FOR ALL

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
UNIVERSAL	 Clear	UNIPSI	2C-1,2  1 FT  €€	 EN166 FT €€	Anti-scratch/anti-fog
	 Smoke	UNIPSF	5-3,1  1 FT €€	 EN166 FT €€	Anti-scratch/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

€€ European standard  Manufacturer name

TECHNOLOGY

B-FLEX


The revolutionary B-Flex technology provides unique flexibility. light, soft and fully pliable, the B-Flex bridge is fully adjustable and perfectly fits all faces thanks to its shape-memory material.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

PACKAGING AND EAN13 CODE		
	UNIPSI	UNIPSF
Individual plastic bag	3660740006525	3660740006532
10 safety spectacles per inner box	3660740106522	3660740106539
300 safety spectacles per outer pack	3660740206529	3660740206536

CHARACTERISTICS	
LENSES	PC - 2,3 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY